
Crane scale KERN HFB











The professional alternative up to 600 kg with rear-facing second display

Features

- II With the TÜV/GS certification mark, the scale meets the requirements of the German Equipment and Product Safety Act (Geräte- und Produktsicherheitsgesetz, GPSG) and has been tested in accordance with EN 13155 (Non-fixed load lifting attachments) and EN 61010-1 (Elektrische Sicherheit)
- High mobility: thanks to battery operation, compact construction and low weight, it is suitable for use in several locations (production, warehouse, dispatch department,...)
- 3 Second display on the rear of the balance
- Hook with safety catch, revolving

- Rechargeable battery pack internal, standard, operating time approx. 30 h, charging time approx. 14 h with mains adapter. Charge indicator using LED
- Data hold function: When the weighing value remains unchanged the weight indicated on the display is automatically "frozen" until the HOLD key is pressed
- Tare: Resets the display to "0" when there is a load on the scale. Now removed or added loads are directly displayed
- 2 Radio remote control standard. Range approx. 20 m. All functions can be selected (excl. ON/OFF). WxDxH 48x10x95 mm. Batteries included 2 x 1,5 V AAA

Technical data

- Superior display size: digit height 25 mm. Bright backlight for easy reading of weight, even from a distance
- · Dimensions housing WxDxH 163x126x158,5 mm
- Precision: 0.2 % from [Max]
- Permissible ambient temperature 0°C / 40°C





















Dimensions Optional Extra Model Weighing Read-Net DKD Calibr. Certificate В D range out weight [Max] [d] DKD approx. KERN kg g kg **KERN** mm mm mm mm HFB 150K50 150 50 3,2 26 25 358 390 963-129 HFB 300K100 25 100 390 963-129 300 3,2 26 358 HFB 600K200 200 3,2 390 963-130 600 26 25 358

